

ED Heating Immersion Circulator

Print Data Sheet



Advantages

Description

o Bright LED temperature display, resolution 0.1 °C

cooling-water connection is also available as an accessory.

- o Keypad for setpoint, switches automatically to the actual value
- o PID1 temperature control
- o Adjustable high temperature cut-out / dry-running protection

Heating Immersion Circulator for any bath tanks up to 50 liters

JULABO Heating Immersion Circulators are available for various bath tanks up to a capacity of 50 litres and come equipped with a bath clamp that fits onto all tanks with a wall thickness up to 26 mm. This clamp allows fast and problem-free assembling for existing as well as new bath tanks. The immersion depth is 16.5 cm (adjustable down to 14.5 cm). The immersed parts are made of high-quality stainless steel or plastic. The pump set, which is available as an accessory, provides pumping to external systems for provision of external temperature tasks. An integrated cooling coil for

Technical Specifications	
Working temperature range	20 100 °C
Temperature control	PID
Temperature stability	±0.03 °C
Display	LED
Display resolution	0.1 °C
Integrated programmer	not available
Heater capacity	2000 W
Pump capacity	Pressure: 0,35 bar Flow rate: 15 l/min
Dimensions (W x L x H)	13 x 15 x 33 cm
Weight	3,3 kg
Ambient temperature	540 °C
Classification according to DIN 12876-1	1 (NFL)

Miscellaneous

Installation cooling coil and pump set for external applications available as accessory.

Order Information

Model: EI

Order no.: 9116000

Available mains power: 230V / 50Hz 115V / 60Hz

100V / 50-60Hz 230V / 60Hz

Sales & Support:



Monday to Friday 7:30 am - 17:00 pm

JULABO Labortechnik GmbH Eisenbahnstrasse 45 77960 Seelbach/Germany Phone +49 7823 51-0 Fax +49 7823 2491 info@julabo.de

Technical changes reserved. Pictures may differ from original.

www.julabo.de